


Calipso LED wall/ceiling 3000K white

0210018A

SPECIFICATIONS



Design By

Neil Poulton

Collection

Design



Specifications

Delivered lumens	2884lm
Light output ratio	50lm/W
Power consumption	58W
Led type	49.8W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V**
Input Voltage	120-277V
Driver	ENEDO - 1 x RCL050-1200A

*Integrated light source **2-wire dimming at 120VAC only

Colors & Finishes

☐ White


Materials

- Fractal shape of an impure geometry
- Direct diffused light output
- Louver in ASA (Acrylonitrile Styrene Acrylate)

Features & Accessories

- Driver is compatible to both 2-wire dimming and 0-10V dimming options
- ADA compliant

Dimensions



Packaging

1 Box

1 x 23-11/16" x 24-1/8" x 7" / 11.42 lbs - 60 cm x 61 cm x 17.5 cm / 5.18 kg

Light distribution

Direct

Luminaire weight

8.95 lbs / 4.06 kg

Warranty

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane